
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☒ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Behr Process Corporation
Product Name: 500 The Stripper (Aerosol) (DISCONTINUED)

MATERIAL SAFETY DATA SHEET

C00141
01 00

MANUFACTURER'S NAME
BEHR PROCESS CORPORATION
3400 Garry Street
Santa Ana, CA 92704

EMERGENCY TELEPHONE NO.
(800) 424-9300

DATE OF PREPARATION
21-JAN-98

INFORMATION TELEPHONE NO.
(714) 545-7101

Section I -- PRODUCT IDENTIFICATION

PRODUCT NUMBER

C00141

HMIS CODES

Health	2*
Flammability	4
Reactivity	0

PRODUCT NAME

500 THE STRIPPER

PRODUCT CLASS

Aerosol Specialty Product

Section II -- HAZARDOUS INGREDIENTS

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Propane 74-98-6	15		1000	PPM	760.00
Methylene Chloride. 75-09-2	63	50	25	PPM	420.00
	STEL		125	PPM	
Toluene. 108-88-3	9	50	100	PPM (Skin)	22.00
	STEL		150	PPM (Skin)	
2-Propanol 67-63-0	11	400	400	PPM	33.00
	STEL	500	500	PPM	

Section III -- PHYSICAL DATA

PRODUCT WEIGHT -- 8.05 lb./gal.	EVAPORATION RATE -- Faster than Ether
SPECIFIC GRAVITY -- 0.97	VAPOR DENSITY -- Heavier than Air
BOILING POINT -- <0 -238 F	MELTING POINT -- N.A.
VOLATILE VOLUME -- 98 %	SOLUBILITY IN WATER -- N.A.
VOLATILE WEIGHT -- 34.89 % (less Federally Exempt Solvents)	
HMIS -- 2 * 4 0	

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	LEL	UEL
Propellant < 0 F	1.0	12.7
EXTINGUISHING MEDIA		
Carbon Dioxide, Dry Chemical, Foam		

Continued on page 2

=====

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

=====

Section V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Overexposure to Methylene Chloride can raise the level of carbon monoxide in the blood.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Cardiovascular problems may be aggravated by overexposure to Methylene Chloride.

EMERGENCY AND FIRST AID PROCEDURES

- | | |
|---------------|---|
| If INHALED: | If affected, remove from exposure. Restore breathing. Keep warm and quiet. |
| If on SKIN: | Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use. |
| If in EYES: | Flush eyes with large amounts of water for 15 minutes. Get medical attention. |
| If SWALLOWED: | Never give anything by mouth to an unconscious person. Give conscious patient several glasses of water. If vomiting is not spontaneous, induce vomiting by having the patient gently touch the back of his throat with a finger. Keep airway clear. Seek medical attention. |

=====

CHRONIC Health Hazards

Methylene Chloride is listed by IARC, NTP, and OSHA. Laboratory animals exposed to high levels of Methylene Chloride in lifetime studies have developed cancer. There is no evidence to date that Methylene Chloride causes cancer in humans.

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, cardiovascular, nervous and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

=====

Section VI -- REACTIVITY DATA

STABILITY -- Stable
CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide, Hydrogen Chloride

HAZARDOUS POLYMERIZATION

Will not occur

=====

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

=====

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Before initial use, consult OSHA's Standard for Occupational Exposure to Methylene Chloride (29 CFR 1910.1052).

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

An air supplied respirator must be worn, unless air monitoring demonstrates vapor/mist concentrations are below permissible limits. Follow respirator manufacturer's directions for respirator use.

PROTECTIVE GLOVES

For intermittent exposure, wear VITON or nitrile gloves recommended by glove manufacturer for protection against materials in Section II. For immersion, wear PVA gloves recommended by glove manufacturer.

Continued on page 4

=====

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

=====

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY

1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====

Section X -- OTHER REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
75-09-2	Methylene Chloride.	63	
108-88-3	Toluene.	9	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.